

Transport trolley, double refrigeration Metos Burlodge RTS C

Serving trolley for portioned meals on trays. Equipped to serve both in cook-serve and cook- chill operations. The system ensure the taste and microbiology quality of the portions - cold meal items are served cold and warm are served warm! All in accordance with current EU HACCP-regulations. The isolated divider wall divides the chamber and each tray in a hot and a cold part with all meal components on the flat tray. Made for usage of ordinary crockery. Efficient convection heating/refrigeration, holding of cold plated foods in advance of heating (cook-chill)

General features:

- Easy daily use: Three different programs (breakfast, lunch, dinner) with 2-phase temperatures and time. Regeneration cycle start manually or timer-controlled. Display with intelligible symbols.
- Light and easy to maneuver: Four vertical, ergonomic handles on each corner. Rubber bumper around the entire trolley base.
- Secure: Digital display shows the chamber temperature in real time and remaining heating cycle. Audible alarm. Surface temperature below +45°C.
- Strong structure: Strong stainless steel AISI304 18/10 frame and inner panels, light weight and shockproof carbon fiber doors reinforced with an aluminum rim. Outer panels antistatic ABS (grey).
- Excellent energy efficiency: high density injected insulation (30 mm). Smart Temp -software considers partial load.
- Hygiene: jet washable, drain with foot pedal. Rated IPX5. Antibacterial material in door latch. Gaskets can be removed without tools for machine dish washing. Wheels with non-marking



elastic rubber tyre. elastic rubber tyre.

Transport trolley, double refrigeration Metos Burlodge RTS C

Product capacity	26 or 30 trays
Item width mm	1025
Item depth mm	780
Item height mm	1715
Package volume	1.742
Unit of volume	m3
Package volume	1.742 m3
Package length	110
Package width	88
Package height	180
Package unit of dimension	cm
Package dimensions (LxWxH)	110x88x180 cm
Net weight	209
Net weight	209 kg
Gross weight	219
Package weight	219 kg
Unit of weight	kg
Connection power kW	6.2
Fuse Size A	11
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Plug
Electrical conn. height mm	1350
Type of the refrigerant	R452a
Quantity of refrigerant g	530
Remarks (refrigeration)	GWP 2141