

Refr./refr. Metos Start MG25/25L TNN HP R290

Two separate refrigerators. Temperature range $-2^{\circ}\text{C} \dots +8^{\circ}\text{C}$

- ambient temperature $+15^{\circ}\text{C} \dots +43^{\circ}$
- EVJ touch controller with big display of maximum 30 mm size numbers, possibility to adjust set temperatures
- overcooling function, keeps the compressor on work 30 minutes without breaks
- able to store up to 3 alarms, device provides the critical temperature values and duration of the alarm
- stainless steel interiors and exterior, except painted galvanised back wall
- rounded inner corners makes it easy to clean the compartments
- fan evaporators are placed under the internal roofs in cabinets
- automatic defrost and hot gas condensate evaporation, manual defrosting also possible
- polyurethane insulation
- hermetic air-condensed compressors in the upper part of the cabinet
- 2 pc 430*530 mm stainless steel grid shelves / cabinet
- grids are easy to remove for cleaning and grid support rail distance is 50 mm
- self closing left handed doors, which stays open when door angle is over 90°
- removable door seals without use of tools
- sturdy adjustable stainless steel feet

Options for extra price:

- grid shelves, slides for grigs, castors



Refr./refr. Metos Start MG25/25L TNN HP R290

Product capacity	138/112 litres
Item width mm	600
Item depth mm	700
Item height mm	2080
Net volume l	150+150 litres acc.to EN16825
Package volume	1.056
Unit of volume	m3
Package volume	1.056 m3
Package length	64
Package width	75
Package height	220
Package unit of dimension	cm
Package dimensions (LxWxH)	64x75x220 cm
Net weight	148
Net weight	148 kg
Gross weight	161
Package weight	161 kg
Unit of weight	kg
Connection power kW	0.875
Fuse Size A	10
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Protection rating (IP)	X4
Type of electrical connection	Plug
Cooling capacity W	850
Type of the refrigerant	R290
Remarks (refrigeration)	Quantity of refr. 66g+50g
Sound level dB	48

Refr./refr. Metos Start MG25/25L TNN HP R290

Raw material	stainless steel
Hinge location	left
Temperature area °C	-2/+8
Rail distance mm	60
Number of chambers	2
Shelf size mm	430x530
Lighting	LED
Cooling unit	With cooling unit
Defrosting	automatic
Temperature probe	No
Fill in trolleys	No
Glass door	No