

# Pizza oven Metos Domitor Pro 830 EM

Metos Domitor Pro 830 EM pizza oven for pizzas' diameter 30 cm. Baking with direct on firestone or indirect in baking trays. Models available for 4/6/9 pizzas. Modularity up to 3 decks. Max temperature can be adjusted between 0...400 °C. Independent control of ceiling and bedplate heating elements. Door in steel with ceramic glass opens downwards. Baking chamber in illuminated irradiating plate and baking surface is made of 14 mm alveolar refractory stone. High thermal resistance insulation in ceramic fiber and eco-friendly rock wool. The oven chamber is illuminated by a halogen lamp. Smoke exhaust: always open.

- two chamber pizza oven, chamber size 630 x 630 mm
- the oven chamber is sized for four 30 cm pizzas
- supplied without stand
- electromechanical control
- temperature adjustment max. 400°C, temperature display
- a brick grate that stores heat well
- separate control for chamber top and bottom heat
- the door opens downwards

ACCESSORIES (to be ordered separately):

- flue
- stand
- wheel set for the stand



## Pizza oven Metos Domitor Pro 830 EM

|                               |                 |
|-------------------------------|-----------------|
| Product capacity              | 8 x 30 cm pizza |
| Item width mm                 | 882             |
| Item depth mm                 | 827             |
| Item height mm                | 686             |
| Package volume                | 0.669           |
| Unit of volume                | m3              |
| Package volume                | 0.669 m3        |
| Package length                | 95              |
| Package width                 | 88              |
| Package height                | 80              |
| Package unit of dimension     | cm              |
| Package dimensions (LxWxH)    | 95x88x80 cm     |
| Net weight                    | 200             |
| Net weight                    | 200 kg          |
| Gross weight                  | 235             |
| Package weight                | 235 kg          |
| Unit of weight                | kg              |
| Connection power kW           | 8.8             |
| Fuse Size A                   | 20              |
| Connection voltage V          | 400             |
| Number of phases              | 3NPE            |
| Frequency Hz                  | 50              |
| Type of electrical connection | Semifixed       |