

Blast freezer cabinet Metos MSB-050-RAR-R290 Right (under counter)

The Metos MSB-050-RAR-R290 blast chilling and freezing cabinet quickly cools raw and cooked food. The food stays fresh and of high quality and, above all, clean. In professional kitchens, special attention must be paid to food safety.

The Metos MSB-050-RAR-R290 is equipped with cooling unit and the refrigerant in this model is R290. The model is without working top and total height is 855mm so it fits under the counter. There are ready-made programs for both chilling and freezing functions, from gentle to very efficient. In addition to these, the user can store the user's own programs. The appliance automatically switches to storage mode at the end of the quick cooling process. Inner and outer lining in easy-to-clean stainless steel. Rounded corners and a bottom plug make cleaning easier.

- capacity 5 x GN 1/1-65, rail distance 70mm
- cooling capacity 18 kg + 90 ° C ... + 3 ° C in 90 minutes, freezing capacity 12 kg + 90 ° C ... - 18 ° C in 240 minutes, stated capacities kg/h are nominal, and cannot be achieved with all food products and circumstances
- under counter model, without working top
- core probe
- programmes for both blast chilling and shock freezing
- when the program ends, the device automatically enters storage mode
- s/s exterior and interior
- cavity with central drain for discharge of washing water
- high-density polyurethane's insulation (aprox. 42 kg/m³), without CFC nor HCFC
- air cooling
- high performance copper-aluminum condenser
- right handed which is not reversible
-



ergonomic handle across entire height of door and magnetic seals on all 4 sides of the door

- heating element in the door frame
- indirect blowing electronic fans, efficient but gentle on food
- defrosting and evaporation water must be direct to the drain
- control and command circuit board, easy to use
- compressor protected by termic overload cut-out with automatic reset
- internal dimensions 670x335x400mm
- 50mm high feet ergonomic handle across entire height of door and magnetic seals on all 4 sides of the door
- heating element in the door frame
- indirect blowing electronic fans, efficient but gentle on food
- defrosting and evaporation water must be direct to the drain
- control and command circuit board, easy to use
- compressor protected by termic overload cut-out with automatic reset
- internal dimensions 670x335x400mm
- 50mm high feet

Blast freezer cabinet Metos MSB-050-RAR-R290 Right (under counter)

| | |
|-------------------------------|------------------------|
| Product capacity | 18kg/12kg/+90...+3/-18 |
| Capacity | 5 x GN1/1-65 |
| Item width mm | 790 |
| Item depth mm | 700 |
| Item height mm | 855 |
| Package volume | 0.715 |
| Unit of volume | m3 |
| Package volume | 0.715 m3 |
| Package length | 83 |
| Package width | 82 |
| Package height | 105 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 83x82x105 cm |
| Net weight | 105 |
| Net weight | 105 kg |
| Gross weight | 145 |
| Package weight | 145 kg |
| Unit of weight | kg |
| Connection power kW | 0.924 |
| Fuse Size A | 10 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | X4 |
| Type of electrical connection | Plug |
| Cooling capacity W | 825 |
| Condensing temperature °C | +45 |
| Evaporation temperature °C | -25 |
| Type of the refrigerant | R290 |

Blast freezer cabinet Metos MSB-050-RAR-R290 Right (under counter)

| | |
|---------------------------|-------------------|
| Quantity of refrigerant g | 150 |
| Sound level dB | 70 |
| Cooling unit | With cooling unit |