

Hand-out shelf, fixed Metos Proff HS-1200

Construction of stainless steel and tempered glass. Glasses are easy to remove and clean.



Hand-out shelf, fixed Metos Proff HS-1200

Item width mm	1195
Item depth mm	210
Item height mm	300
Package volume	0.01
Unit of volume	m3
Package volume	0.01 m3
Package length	0
Package width	0
Package height	0
Package unit of dimension	cm
Package dimensions (LxWxH)	0x0x0 cm
Net weight	16
Net weight	16 kg
Gross weight	16
Package weight	16 kg
Unit of weight	kg

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95

Hand-out shelf, fixed Metos Proff HS-1200

Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	0.6
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	2.7
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	13 GN1/1-100
Number of chambers	3
Power range kW	0.6
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.073
Unit of volume	m3
Package volume	1.073 m3
Package length	130

Hand-out shelf, fixed Metos Proff HS-1200

Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	130x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	6.3
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	13 GN1/1-100
Number of chambers	3
Power range kW	1.4
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	1200x650mm plane+13 GN1/1-100
Item width mm	1200
Item depth mm	650

Hand-out shelf, fixed Metos Proff HS-1200

Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	6.1
Protection rating (IP)	43
Type of electrical connection	Plug
Cleaning	hand wash
GN size	13 GN1/1-100
Number of chambers	3
Power range kW	1.4
Lighting	without lighting
Fill in trolleys	No
Humidification	No

Hand-out shelf, fixed Metos Proff HS-1200

Timer	No
-------	----

Hand-out shelf, fixed Metos Proff HS-1200

Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	119
Package weight	119 kg
Unit of weight	kg
Connection power kW	1.4
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	6.3
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	8
Power range kW	1.4

Hand-out shelf, fixed Metos Proff HS-1200

Lighting	without lighting
Amount of drawers	8
Fill in trolleys	No
Humidification	No

Timer	No
-------	----

Hand-out shelf, fixed Metos Proff HS-1200

Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.031
Unit of volume	m3
Package volume	1.031 m3
Package length	125
Package width	75
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x75x110 cm
Net weight	95
Net weight	95 kg
Gross weight	95
Package weight	95 kg
Unit of weight	kg
Connection power kW	0.6
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	2.7
Protection rating (IP)	43
Type of electrical connection	Plug

Hand-out shelf, fixed Metos Proff HS-1200

Cleaning	hand wash
Number of chambers	8
Power range kW	0.6
Lighting	without lighting
Fill in trolleys	No

Humidification	No
Timer	No

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	3xGN1/1-210 + 9XGN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.963
Unit of volume	m ³
Package volume	0.963 m ³
Package length	125
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x70x110 cm
Net weight	85
Net weight	85 kg
Gross weight	93
Package weight	93 kg
Unit of weight	kg
Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60

Hand-out shelf, fixed Metos Proff HS-1200

Startup current A	9.5
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	3xGN1/1-210 + 9XGN1/1-100
Number of chambers	3

Power range kW	2.2
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	3xGN1/1-210 + 9XGN1/1-100
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.963
Unit of volume	m3
Package volume	0.963 m3
Package length	125
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	125x70x110 cm
Net weight	95
Net weight	95 kg
Gross weight	105
Package weight	105 kg
Unit of weight	kg

Hand-out shelf, fixed Metos Proff HS-1200

Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Startup current A	9.8
Protection rating (IP)	43
Type of electrical connection	Plug
Function	warm

GN size	3xGN1/1-210 + 9XGN1/1-100
Power range kW	2.2
Lighting	without lighting
Type of display	with doors
Upper part	without upper part
Model	Proff
Amount of cabinets	3
Stowage	shelves

Hand-out shelf, fixed Metos Proff HS-1200

Product capacity	3 X GN1/1-150 bain marie
Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	0.702
Unit of volume	m3
Package volume	0.702 m3
Package length	120
Package width	65
Package height	90
Package unit of dimension	cm
Package dimensions (LxWxH)	120x65x90 cm

Hand-out shelf, fixed Metos Proff HS-1200

Net weight	85
Net weight	85 kg
Gross weight	85
Package weight	85 kg
Unit of weight	kg
Connection power kW	1.65
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60

Startup current A	7.2
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	3 X GN1/1-150
Power range kW	1.65
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No