

Upper shelf Proff US-1600- 2L

Construction and upper shelf made of stainless steel. Width of upper shelf 280 mm

- double-sided sneeze guard of tempered glass
- LED light



Upper shelf Proff US-1600-2L

Item width mm	1600
Item depth mm	507
Item height mm	405
Package volume	0.369
Unit of volume	m3
Package volume	0.369 m3
Package length	162
Package width	53
Package height	43
Package unit of dimension	cm
Package dimensions (LxWxH)	162x53x43 cm
Net weight	17
Net weight	17 kg
Gross weight	17
Package weight	17 kg
Unit of weight	kg
Connection power kW	0.03
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	0.2
Protection rating (IP)	20
Type of electrical connection	Semifixed

Upper shelf Proff US-1600-2L

Item width mm	1600
Item depth mm	650
Item height mm	900
Package volume	1.271
Unit of volume	m3

Upper shelf Proff US-1600-2L

Package volume	1.271 m3
Package length	165
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	165x70x110 cm
Net weight	85
Net weight	85 kg
Gross weight	105
Package weight	105 kg
Unit of weight	kg
Connection power kW	2.8
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	13
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	GN4/1 210 mm + 12 GN1/1-100
Number of chambers	4
Power range kW	2.8
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

Upper shelf Proff US-1600-2L

Item width mm	1600
---------------	------

Upper shelf Proff US-1600-2L

Item depth mm	650
Item height mm	900
Package volume	1.271
Unit of volume	m ³
Package volume	1.271 m ³
Package length	165
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	165x70x110 cm
Net weight	95
Net weight	95 kg
Gross weight	115
Package weight	115 kg
Unit of weight	kg
Connection power kW	2.8
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	13
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	4x1/1 + 12 GN1/1-100
Number of chambers	4
Power range kW	2.8
Lighting	without lighting

Upper shelf Proff US-1600-2L

Fill in trolleys	No
Humidification	No
Timer	No

Upper shelf Proff US-1600-2L

Item width mm	1600
Item depth mm	650
Item height mm	900
Package volume	0.965
Unit of volume	m3
Package volume	0.965 m3
Package length	165
Package width	65
Package height	90
Package unit of dimension	cm
Package dimensions (LxWxH)	165x65x90 cm
Net weight	100
Net weight	100 kg
Gross weight	100
Package weight	100 kg
Unit of weight	kg
Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	9.6
Protection rating (IP)	43
Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash

Upper shelf Proff US-1600-2L

GN size	GN4/1-210
Power range kW	2.2

Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No

Upper shelf Proff US-1600-2L

Item width mm	1600
Item depth mm	650
Item height mm	900
Package volume	0.965
Unit of volume	m3
Package volume	0.965 m3
Package length	165
Package width	65
Package height	90
Package unit of dimension	cm
Package dimensions (LxWxH)	165x65x90 cm
Net weight	60
Net weight	60 kg
Gross weight	67
Package weight	67 kg
Unit of weight	kg
Connection power kW	2.2
Fuse Size A	16
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50
Startup current A	10
Protection rating (IP)	43

Upper shelf Proff US-1600-2L

Type of electrical connection	Plug
Operation type	electromechanical
Cleaning	hand wash
GN size	GN1/1-210

Power range kW	2.2
Lighting	without lighting
Fill in trolleys	No
Humidification	No
Timer	No