

Hight adj. for brat pan Metos Futura H

Adjustment range 800...950 mm (from floor to upper edge of pan, lid open).



Hight adj. for brat pan Metos Futura H

Package volume	0.01
Unit of volume	m3
Package volume	0.01 m3
Package length	0
Package width	0
Package height	0
Package dimensions (LxWxH)	0x0x0
Net weight	1
Net weight	1 kg
Gross weight	1.5
Package weight	1.5 kg
Unit of weight	kg
Connection power kW	0.345
Fuse Size A	1.5
Connection voltage V	230

Hight adj. for brat pan Metos Futura H

Product capacity	37 L, frying surface 790 x 530
Capacity	850×806 ×954
Item width mm	850
Item depth mm	806
Item height mm	954
Package volume	1.058
Unit of volume	m3
Package volume	1.058 m3
Package length	98
Package width	90
Package height	120
Package unit of dimension	cm
Package dimensions (LxWxH)	98x90x120 cm
Net weight	170

Hight adj. for brat pan Metos Futura H

Net weight	170 kg
Gross weight	200
Package weight	200 kg
Unit of weight	kg
Connection power kW	10.5
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Startup current A	15
Protection rating (IP)	X3
Type of electrical connection	Fixed
Electrical conn. height mm	360
Power type	electric
Raw material	Stainless steel
Operation type	electromechanical
Cleaning	hand wash
Temperature area °C	50-250
Pan volume L	85
Tilting	electric
Temperature probe	No
Oil filtering	No
Timer	No

Hight adj. for brat pan Metos Futura H

Product capacity	75 L, frying surface 790 * 530
Item width mm	850
Item depth mm	806
Item height mm	954
Package volume	1.058
Unit of volume	m3

Hight adj. for brat pan Metos Futura H

Package volume	1.058 m3
Package length	98
Package width	90
Package height	120
Package unit of dimension	cm
Package dimensions (LxWxH)	98x90x120 cm
Net weight	170
Net weight	170 kg
Gross weight	200
Package weight	200 kg
Unit of weight	kg
Connection power kW	10.5
Fuse Size A	16
Connection voltage V	400/230
Number of phases	3NPE
Frequency Hz	50
Startup current A	15
Protection rating (IP)	X3
Type of electrical connection	Fixed
Electrical conn. height mm	360
Power type	electric
Operation type	electromechanical
Cleaning	hand wash
Tilting	electric
Temperature probe	No
Oil filtering	No
Timer	No

Hight adj. for brat pan Metos Futura H

Package volume	0.01
Unit of volume	m3

Hight adj. for brat pan Metos Futura H

Package volume	0.01 m3
Package length	0
Package width	0
Package height	0
Package dimensions (LxWxH)	0x0x0
Net weight	2
Net weight	2 kg
Gross weight	2
Package weight	2 kg
Unit of weight	kg
Power type	electric
Operation type	electromechanical
Cleaning	hand wash
Temperature area °C	50-250
Tilting	manual
Temperature probe	No
Oil filtering	No
Timer	No

Hight adj. for brat pan Metos Futura H

Product capacity	100 L, surface 1040 * 530
Item width mm	1100
Item depth mm	806
Item height mm	954
Package volume	1.318
Unit of volume	m3
Package volume	1.318 m3
Package length	122
Package width	90
Package height	120
Package unit of dimension	cm

Hight adj. for brat pan Metos Futura H

Package dimensions (LxWxH)	122x90x120 cm
Net weight	195
Net weight	195 kg
Gross weight	225
Package weight	225 kg
Unit of weight	kg
Connection power kW	15
Fuse Size A	25
Connection voltage V	400/230
Number of phases	3NPE
Frequency Hz	50
Startup current A	22
Protection rating (IP)	X3
Type of electrical connection	Fixed
Electrical conn. height mm	360
Power type	electric
Operation type	electromechanical
Cleaning	hand wash
Tilting	electric
Temperature probe	No
Oil filtering	No
Timer	No

Hight adj. for brat pan Metos Futura H

Product capacity	50 L, total surface 1040 * 530
Item width mm	1100
Item depth mm	806
Item height mm	954
Package volume	1.318
Unit of volume	m3
Package volume	1.318 m3

Hight adj. for brat pan Metos Futura H

Package length	122
Package width	90

Package height	120
Package unit of dimension	cm
Package dimensions (LxWxH)	122x90x120 cm
Net weight	195
Net weight	195 kg
Gross weight	225
Package weight	225 kg
Unit of weight	kg
Connection power kW	15.1
Fuse Size A	25
Connection voltage V	400/230
Number of phases	3NPE
Frequency Hz	50
Startup current A	21.8
Protection rating (IP)	X3
Type of electrical connection	Fixed
Electrical conn. height mm	360
Power type	electric
Operation type	electromechanical
Cleaning	hand wash
Pan volume L	110
Temperature probe	No
Oil filtering	No
Timer	No