

Bioavfall uppslagare Metos IMC WasteStation

WasteStation reduces the mass of food waste by up to 60%
Higher capture rate - High capture rates improve the quality of the "grey water" going to drain (less suspended solid particles), aiding local water authority approval. Self rinse system – following each operation the machine undertakes a quick rinse cycle preventing any build up of food. Range of screen sizes - Giving the option to recover greater waste levels or concentrate on pure volume reduction. Fully enclosed system - prevents food entering the unit, keeping the machine clean and free of waste and reducing operational noise. Self cleaning operation - WasteStation can undertake a thorough clean ensuring the whole system is free of food and grease, vastly reducing the labour time required to operate the machine. Self emptying – this eliminates the need for staff to empty the auger assembly reducing labour times required to operate the machine Visual control panel - Kitchens are a noisy environment, WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation. Intelligent electronic sensor – detects when the bin is full..

Standard equipments: 2 biowaste bins



Bioavfall oppslagare Metos IMC WasteStation

Bredde mm	1000
Dyp mm	700
Høyde mm	900
Pakkevolum inkl. emballasje	0,77
Volumenhet	m3
Pakkevolum	0,77 m3
Lengde på forpakning	100
Bredde på forpakning	70
Høyde på forpakning	110
Forpakkingsstørrelse	cm
Transport mål (LxDxH)	100x70x110 cm
Netto vekt	192
Net weight with unit	192 kg
Bruttovekt	210
Vekt inkl. emballasje	210 kg
Vektenhet	kg
Tilkoblingseffekt kW	4,1
Sikringsstørrelse A	16
Spenning V	400
Antall faser	3NPE
Frekvens Hz	50
Type elektrisk tilkobling	Sikkerhetsbryter
Kaldt vann diam.	15
Kaldt vann, min trykk kPa	200
Varmt vann, diam.	15
Varmt vann, min trykk kPa	200
Avløp, diam.	54
Avløp, tilkoblingshøyde mm	150