

Bioavfall uppslagare Metos IMC WasteStation

WasteStation reduces the mass of food waste by up to 60%
Higher capture rate - High capture rates improve the quality of the "grey water" going to drain (less suspended solid particles), aiding local water authority approval. Self rinse system – following each operation the machine undertakes a quick rinse cycle preventing any build up of food. Range of screen sizes - Giving the option to recover greater waste levels or concentrate on pure volume reduction. Fully enclosed system - prevents food entering the unit, keeping the machine clean and free of waste and reducing operational noise. Self cleaning operation - WasteStation can undertake a thorough clean ensuring the whole system is free of food and grease, vastly reducing the labour time required to operate the machine. Self emptying – this eliminates the need for staff to empty the auger assembly reducing labour times required to operate the machine. Visual control panel - Kitchens are a noisy environment, WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation. Intelligent electronic sensor – detects when the bin is full..

Standard equipments: 2 biowaste bins



Bioavfall uppslagare Metos IMC WasteStation

Bredd mm	1000
Djup mm	700
Höjd mm	900
Paketvolym	0,77
Volymenhet	m ³
Paketvolym	0,77 m ³
Längd på förpackning	100
Bredd på förpackning	70
Höjd på förpackning	110
Förpackningsstorlek	cm
Dimensioner på förpackning (LxBxH)	100x70x110 cm
Nettovikt	192
Nettovikt med ental	192 kg
Bruttovikt	210
Vikt inkl. emballage	210 kg
Viktenhet	kg
Anslutningseffekt kW	4,1
Säkringsstorlek A	16
Spänning V	400
Antal faser	3NPE
Frekvens Hz	50
Typ av anslutning	Säkerhetsbrytare
Kallvatten diameter	15
Kallvatten, min tryck kPa	200
Varmvatten, diameter	15
Varmvatten, min tryck kPa	200
Avlopp, diameter	54
Avlopp, höjd mm	150