

Combi cutter Metos CC-32S 230V1~

Metos Combi Cutter CC-32S Combined Vegetable Preparation machine, process up to 2 kg/minute and vertical Cutter, volume 3 litre. Specification: Combination machine with half-moon feed cylinder and stainless steel bowl, made to process 2kg/minute or 10-80 portions/day. Machine has two speeds with switch depending on what preparation top is mounted. Machine is controlled with a turning knob instead of buttons. Vegetable preparation top is of 0.9 litre with a tube feeder of 53mm in diameter. Bowl is 3 litre and has a scraper system with three scrapers. Knives for bowl cutter are serrated- The machine base and the knife chamber are made of ABS-plastic. Machine is controlled with a turning knob instead of buttons. Cutting tools are made of stainless steel, 185mm in diameter and washable in dishwasher. Motor rotates the cutting blade clockwise via a self-tensioned toothed belt. Machine has handles for easy mobility. Function: Machine for slicing, shredding, grating and cutting julienne as well as grinding, chopping, blending and mixing. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, meat, fish, etc. Capacity: Up to 80 portions/day and up to 2/kg/minute. 0,9 litre feed cylinder, 53mm tube feeder for elongated products. Bowl: 3 litre. Material: Machine base and knives chamber: ABS-plastic. Feeder top: polycarbonate and polyamide. Cutting tools: stainless steel. Ejector plate: acetal. Bowl: stainless steel. Knife unit: acetal. Lid and Scraper system: Xylex. Motor: 1.0 kW. Two speeds (500rpm, 1450 rpm) 220-240 V, single phase, 50-60 Hz. Transmission: Toothed belt.



Thermal protection. Power Supply: Earthed, single phase, 10A. Fuse: 10 A delayed action fuse. Standards: EN 1678+A1:2010. NSF/ANSI Standard 8. Safety: 2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011 CE approved. Two safety switches, machine safety: IP34 Thermal protection. Power Supply: Earthed, single phase, 10A. Fuse: 10 A delayed action fuse. Standards: EN 1678+A1:2010. NSF/ANSI Standard 8. Safety: 2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011 CE approved. Two safety switches, machine safety: IP34

Combi cutter Metos CC-32S 230V1~

Item width mm	285
Item depth mm	350
Item height mm	465
Package volume	0.069
Unit of volume	m3
Package volume	0.069 m3
Package length	30
Package width	49
Package height	47
Package unit of dimension	cm
Package dimensions (LxWxH)	30x49x47 cm
Net weight	7.6
Net weight	7.6 kg
Gross weight	9.5
Package weight	9.5 kg
Unit of weight	kg
Connection power kW	1
Fuse Size A	10
Connection voltage V	230
Number of phases	1NPE
Frequency Hz	50/60
Protection rating (IP)	34
Type of electrical connection	Plug
Electrical conn. height mm	25
Blade diameter mm	185
Portions / 24 h	80
Power range kW	1
Speed rpm	1450