

# Dishwasher Metos LUX Hygiene+ 60EL PS XP

High-Tech double skin under-counter dishwasher is designed for heavy duty use in professional kitchens and restaurants. The digital control panel is easy to use and its signal lights indicate the different cycles. Diagnostic function supports self-monitoring.

In the PLUS version the intermediate break tank is filled by the rinsing water. In the boiler there is no pressure. The rinsing water will be heated up to the desired temperature. Final rinsing will take place with the booster pump. No water is added into the boiler during the final rinse. The temperature of the rinsing water is all the time e.g. 85°C. The boiler will be filled only after the rinsing is finished.

PLUS system is guaranteeing the temperature and best result of the final rinse not depending of the inlet water pressure.

- can be connected for hot or cold water connection
- comes with cable, Plug not included
- four wash programs (1, 2, 3 and 5 minutes)
- automatic cleaning program
- max height for dishes 325 mm
- able to wash GN1/1 container
- signal lights indicate the different cycles and temperatures
- diagnostic function ensures a sufficiently high temperature in the final rinse
- rounded edges in the tank facilitate cleaning
- easy to remove wash arm
- water consumption 2,3 l/cycle (water pressure 200kPa)
- acoustic and thermal insulation keeps the noise level and the surface temperature low
- rack size 500x500 mm
- boiler capacity 5,7 l
- tank volume 16,5 l

Delivery includes:

-



detergent dispenser

- rinse aid dispenser
- basket for plates
- basket for glasses
- cutlery cylinder
- connection hose for tap water
- soft start: progressive start of the wash pump
- break tank
- HYGIENE+ thermodisinfection cycle
- drain pump

Optional (to be ordered separately):

- stand
- pressure boosting pump (to be ordered together with the dishwasher)
- steel reinforced hose
- extra racks
- pre-wash tables and basket trolleys detergent dispenser
- rinse aid dispenser
- basket for plates
- basket for glasses
- cutlery cylinder
- connection hose for tap water
- soft start: progressive start of the wash pump
- break tank
- HYGIENE+ thermodisinfection cycle
- drain pump

Optional (to be ordered separately):

- stand
- pressure boosting pump (to be ordered together with the dishwasher)
- steel reinforced hose
- extra racks
- pre-wash tables and basket trolleys

## Dishwasher Metos LUX Hygiene+ 60EL PS XP

Item width mm	600
Item depth mm	610
Item height mm	850
Package volume	0.451
Unit of volume	m3
Package volume	0.451 m3
Package length	68
Package width	67
Package height	99
Package unit of dimension	cm
Package dimensions (LxWxH)	68x67x99 cm
Net weight	63.5
Net weight	63.5 kg
Gross weight	72
Package weight	72 kg
Unit of weight	kg
Connection power kW	6.65
Fuse Size A	16
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Electrical conn. height mm	45
Cold water conn. height mm	65
Hot water diam.	3/4"
Hot water flow l/min	10
Hot water conn. height mm	45
Drain diameter	24
Drain flow l/s	3

## Dishwasher Metos LUX Hygiene+ 60EL PS XP

Drain conn. height mm	65
Sound level dB	62
Boiler power kW	4.5
Boiler volume L	5.7
Operation type	electronical
Cleaning	washing program
Washing basket size mm	500x500
Programmability	ready programs;programmable
Amount of programs	4
Insulation	insulated
Method of washing	normal wash;glass wash
Drain pump	Yes
Model	LUX 60EL