

Cold Basin Metos Drop-In CB 800

Cold basin GN 2/1, depth 160 mm. Drop-in model without side panels

- structure of the basin totally seamless and all the corners have been rounded for easier cleaning
- there is an outlet valve on the bottom of the basin with hose length of 1 m
- basin's edge is 15 mm above the furniture's top plate



Cold Basin Metos Drop-In CB 800

Product capacity	2 x GN 1/1
Item width mm	800
Item depth mm	650
Item height mm	640
Package volume	0.411
Unit of volume	m ³
Package volume	0.411 m ³
Package length	85
Package width	70
Package height	69
Package unit of dimension	cm
Package dimensions (LxWxH)	85x70x69 cm
Net weight	47
Net weight	47 kg
Gross weight	52
Package weight	52 kg
Unit of weight	kg
Connection power kW	0.31
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50
Startup current A	2
Protection rating (IP)	43
Type of electrical connection	Plug
Drain diameter	21/16
Type of the refrigerant	R290
Quantity of refrigerant g	65
Remarks (misc.)	drop-in hole 750x575 mm

Cold Basin Metos Drop-In CB 800

Function	cold
GN size	2GN1/1
Power range kW	0.31
Defrosting	automatic

metos

DROP-IN COLD BASIN

CODE	DROP IN OPENINGS		NET WEIGHT
4138646	DI-CB 450	358mm x 575mm	38 kg
4138656	DI-CB 800	682mm x 575mm	47 kg
4138666	DI-CB 1200	1007mm x 575mm	56 kg
4138674	DI-CB 1600	1332mm x 575mm	65 kg

The length of the connection cable is 3,2 m.

When constructing the counter, an opening for the connection cable must be considered. The opening must be at least the size of a plug (diameter min. 40 mm). In addition, the edges of the opening must be finished to make sure that the connection cable is not damaged by rubbing against the opening edge.

Drain: 22/16 mm
Unit is fitted with a 1 m drain hose

The counter, where drop-in units are installed, must be damp-proof and strong enough to bear the appliance weight.

SERVICE- /VENTILATION DDDR
The grid must be larger in size than the condenser area, i.e. >0,09 m². At least 50% of this area must be perforated.

Flow trough air circulation is recommended by fitting similar grid on the other side of the unit.

