

Cold Display Metos Halo 2SC1200 LED

2-sided cold LED display with square-shaped design and effective refrigeration made of plexi glass. Cold display is intended for the short-term storage and distribution of prerefrigerated foodstuffs and beverages

- LED light under front of each shelf
- self-service display with light-weighed doors with handles
- refrigerated basin 104 mm (basin 534x657, fits 3 x GN1/1-65 without additional basin supports)
- airflow cools efficiently basin and 2 glass shelves
- tested in climate class 3 (temperature +25 $^{\circ}$ C and humidity 60 %)
- basin easy to remove and clean
- glass shelves made of hardened glass
- automatic evaportation system
- adjustable feet +15 /- 45mm
- stainless steel frame structure
- GN-measured cold cabinet, capacity: 10 x GN1/1-65

Accessories/features, to be ordered separately:

- handle-free doors
- laminated panelling
- flat or tube-shaped tray slides
- kick plates
- air flow grid
- adaptation for central cooling and drainage
- covering plate in front to achieve even colder display temperatures





Cold Display Metos Halo 2SC1200 LED

Item width mm	1200
Item depth mm	650
Item height mm	1500
Package volume	1.555
Unit of volume	m3
Package volume	1.555 m3
Package length	122
Package width	72
Package height	177
Package unit of dimension	cm
Package dimensions (LxWxH)	122x72x177 cm
Net weight	212.63
Net weight	212.63 kg
Gross weight	222
Package weight	222 kg
Unit of weight	kg
Connection power kW	1.1
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50
Protection rating (IP)	43
Type of the refrigerant	R290
Quantity of refrigerant g	140