

# Espresso machine Metos Classe 5 ECO USB 2GR Compact Tall

Metos Classe 5 ECO USB 2GR Compact Tall is an automatic espresso machine equipped with an insulated boiler, which prevents unintentional heat loss for an increased thermal performance and power efficiency, guarantees an energy saving of 15%. Its dimensioning allows dispensing into tall drinking glasses and take-away mugs (maximum height 14.5 cm). In the design of the Compact models, special attention has been paid to efficient use of space. The espresso machine with two coffee groups, two steam taps and a hot water tap is only 611 mm wide. The device is well suited for use in, for example, a small café, restaurant or hotel.



Clear buttons and built-in automation make it easy to use. The daily cleaning cycle is automatic and finishes in five minutes. Black side panels, shiny stainless steel that dominates the front and clearly distinguishable steam tap levers give the machine a stylish look. It only takes three minutes to remove the body panels and cup tray to access the main internal parts.

Patented Steady Brew (SB) technology is the evolution of the traditional thermosiphon system and introduces a set of innovative features designed to improve the performance of all single-boiler espresso machines. By keeping the water temperature stable during extraction, Steady Brew guarantees excellent thermal stability, reliability and maximum repeatability, both during busy periods and in low usage conditions.

- two brewing units, two steam taps and a hot water tap
- possibility to use tall (<14.5 cm) drinking glasses and regular cups

-

insulated ECO boiler size 5 liters

- separate gauges for boiler and pump pressures
- USB port
- black ABS plastic side panels protect the machine from knocks
- front panel in mirror-polished stainless steel
- clear and easy to use keyboard
- to facilitate maintenance, the technical components are positioned so that they can be exposed by removing the panels from the front of the device in 3 minutes
- easy to clean

DELIVERY INCLUDES:

- two ergonomically shaped filter holders for one cup and two cups (8,5 gr. ja 16 gr. filter baskets)
- a pull-out dosing level that allows the low cups to be brought to the correct dosing height

ACCESSORIES (to be ordered separately):

- filter holder for POD coffee capsules
- water filter
- barista tool set
- knock-box coffee waste drawer
- espresso bean grinder

Options (to be ordered separately)

- C-lever steaming function to speed up milk frothing (single or double)
- LED lights
- Telemetry
- I- steam DI
- cup warmer
- stone grey or ice white coloring insulated ECO boiler size 5 liters
- separate gauges for boiler and pump pressures
- USB port
- black ABS plastic side panels protect the machine from knocks
- front panel in mirror-polished stainless steel
- clear and easy to use keyboard
- to facilitate maintenance, the technical components are positioned so that they can be exposed by removing the panels from the front of the device in 3 minutes
- easy to clean

DELIVERY INCLUDES:

- two ergonomically shaped filter holders for one cup and two cups (8,5 gr. ja 16 gr. filter baskets)
- a pull-out dosing level that allows the low cups to be brought to the correct dosing height

ACCESSORIES (to be ordered separately):

- filter holder for POD coffee capsules
- water filter
- barista tool set
- knock-box coffee waste drawer
- espresso bean grinder

Options (to be ordered separately)

- C-lever steaming function to speed up milk frothing (single or double)
- LED lights
- Telemetry
- I- steam DI

- cup warmer

- stone grey or ice white coloring

## Espresso machine Metos Classe 5 ECO USB 2GR Compact Tall

Item width mm	611
Item depth mm	539
Item height mm	520
Package volume	0.197
Unit of volume	m3
Package volume	0.197 m3
Package length	65
Package width	55
Package height	55
Package unit of dimension	cm
Package dimensions (LxWxH)	65x55x55 cm
Net weight	55
Net weight	55 kg
Gross weight	65
Package weight	65 kg
Unit of weight	kg
Connection power kW	2.9
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50/60
Electrical conn. inlet	Bottom
Remarks (electrical)	available only in 230V 1phase
Cold water diam.	G3/8
Cold water flow l/min	4
Cold water min pressure kPa	100
Cold water max pressure kPa	600
Cold water conn. inlet	Bottom
Drain diameter	14

## Espresso machine Metos Classe 5 ECO USB 2GR Compact Tall

Floor drain needed

Yes

Sound level dB

70