

# Coffee brewer Metos CBS-1252 Plus with two brewing units

The Metos CBS-1252 Plus coffee brewer is a perfect hot beverage solution for medium- to large-sized venues such as Banquet Halls, Cafeterias and Restaurants. Designed specifically for high-volume batch brewing. Batch buttons are pre-programmed at the factory. If desired the USB port can be used to upload and download recipes.

Cascading spray dome is a patented design which provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.

ECO mode reduces tank temperature during periods of non-operation to cut down on electricity usage.

Plastic brew basket with a capacity of 340 grams and advanced design to provide a deeper bed depth and superior thermal insulation for better extraction.

- two brewing units for two thermos
- capacity: 114 l/h. Cups/hour when factory setting is used: 481 x 236 ml, 320 x 355 ml, 240 x 473 ml or 192 x 591 ml
- brewing time 2-12 minutes (factory set 5,5 min brew time, 0% prewet, 93°C water, 3 l batch)
- can be used with a 6 litres Luxus thermos
- fixed water connection
- manual hot water tap, on 310 mm height from the table
- plastic brew basket, on 570 mm height from the table
- automatic water filling
- Push Button Interface
- pre-wetting, pulse brew, drip delay, brew time and brew volume programmable
- descale indicator
- ECO mode
- USB
- laser welded tank, 39,7 litres

Extra accessories: (will be charged separately)

- 6 litres Luxus thermos
- filter papers F001
- 



brew basket

- water filter cartridges brew basket

- water filter cartridges

## Coffee brewer Metos CBS-1252 Plus with two brewing units

Product capacity	2 x 6 litres thermos
Item width mm	556
Item depth mm	435/572
Item height mm	937
Package volume	0.396
Unit of volume	m3
Package volume	0.396 m3
Package length	61
Package width	69
Package height	94
Package unit of dimension	cm
Package dimensions (LxWxH)	61x69x94 cm
Net weight	35
Net weight	35 kg
Gross weight	44
Package weight	44 kg
Unit of weight	kg
Connection power kW	13.8
Fuse Size A	22
Connection voltage V	400/230
Number of phases	3NPE
Frequency Hz	50
Type of electrical connection	Semifixed
Remarks (electrical)	no cable with machine
Cold water diam.	3/8"
Cold water flow l/min	5
Cold water min pressure kPa	138
Cold water max pressure kPa	517
Drain diameter	19

## Coffee brewer Metos CBS-1252 Plus with two brewing units

Drain conn. inlet	Behind
Floor drain needed	Yes
Cleaning	hand wash
Data transfer	USB
Programmability	programmable
Portion size	2x6 l