

Bakery plate, perfor. Non- stick 450x600

MG4131216

Bakery plate, perfor.Non-stick 450x600

| | |
|----------------------------|--------------|
| Item width mm | 450 |
| Item depth mm | 600 |
| Item height mm | 2 |
| Package volume | 0.001 |
| Unit of volume | m3 |
| Package volume | 0.001 m3 |
| Package length | 45 |
| Package width | 60 |
| Package height | 0.2 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 45x60x0.2 cm |
| Net weight | 1.5 |
| Net weight | 1.5 kg |
| Gross weight | 1.5 |
| Package weight | 1.5 kg |
| Unit of weight | kg |

Bakery plate, perfor.Non-stick 450x600

| | |
|----------------------------|--------------------|
| Product capacity | 2xGN2/1 or 4xGN1/1 |
| Capacity | 4xGN1/1 or 2xGN2/1 |
| Item width mm | 800 |
| Item depth mm | 800 |
| Item height mm | 460 |
| Package volume | 0.53 |
| Unit of volume | m3 |
| Package volume | 0.53 m3 |
| Package length | 95 |
| Package width | 90 |
| Package height | 62 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 95x90x62 cm |

Bakery plate, perfor.Non-stick 450x600

| | |
|-------------------------------|-------------------|
| Net weight | 60 |
| Net weight | 60 kg |
| Gross weight | 75 |
| Package weight | 75 kg |
| Unit of weight | kg |
| Connection power kW | 7.6 |
| Fuse Size A | 16 |
| Connection voltage V | 400 |
| Number of phases | 3NPE |
| Frequency Hz | 50 |
| Startup current A | 10.9 |
| Type of electrical connection | Semifixed |
| Electrical conn. height mm | 250 |
| Cold water diam. | R 3/4" |
| Cold water conn. height mm | 25 |
| Drain diameter | 16 |
| Power type | electric |
| Raw material | Stainless steel |
| Operation type | electromechanical |
| Hinge location | left |
| Cleaning | hand wash |
| GN size | 1/1 / 2/1 |
| Temperature area °C | 50-300 |
| Max temperature °C | 300 |
| Power range kW | 7.6 |
| Temperature probe | No |
| Fill in trolleys | No |
| Hand shower | No |
| Descaling | No |

Bakery plate, perfor. Non-stick 450x600

Humidification

Yes

Timer

Yes