

Induction range D72/10GCII with open cupboard

The Metos Diamante 70 D72/10GCII induction range with an open cupboard has two Ø230 mm size 3.5 kW cooking zones. Cooking zones - in which the temperature can be regulated via control knobs - have been marked on the 6mm thick hob made of unbreakable ceramic glass. An induction range works by only transferring inductive heat from the hob directly to the cooking vessel. Heat does not accumulate within the hob; only the bottom of the pot and the food in the pot or vessel warms up. The hob around the vessels remains cold, which makes using an induction range fast and safe. Cleaning is also easy, since food does not burn onto a cold hob. In addition, the rear of the range is at an incline, which prevents splashes from flowing behind the range.

Every detail of the strong, stylish and hygienic restaurant range series Metos Diamante 70 has been planned as an efficient and functioning solution, from pre-treatment to the preparation of the food itself, without forgetting the need to easily clean the range. Diamante 70 series ranges are available as a table top model as well as with its own cupboard, as single or multiple combined units, and are suitable for use in small to mid-sized to large kitchens. Laser cut range working surfaces allow for the seamless joining together of units into cleanly connected islands or lines in places of heavy use, such as large kitchens.

- two Ø230 mm cooking zones (3.5 kW / cooking zone)
- open cupboard
- Large splash proof control knobs
- the exterior and feet are made from stainless steel
- adjustable height



850...920 mm

- overheating protection

EXTRA ACCESSORIES (can be ordered separately):

- cupboard doors;
- cupboard doors for utensil frames;
- utensil frames; knife rack, utensil rack, spice rack frame, spice jar rack;
- drawer for the cupboard;
- cupboard guide rails (6 guide rails);
- cupboard with a heated bottom;
- socket;
- side panels. 850...920 mm
- overheating protection

EXTRA ACCESSORIES (can be ordered separately):

- cupboard doors;
- cupboard doors for utensil frames;
- utensil frames; knife rack, utensil rack, spice rack frame, spice jar rack;
- drawer for the cupboard;
- cupboard guide rails (6 guide rails);
- cupboard with a heated bottom;
- socket;
- side panels.

Induction range D72/10GCII with open cupboard

Item width mm	400
Item depth mm	730
Item height mm	870
Package volume	0.349
Unit of volume	m3
Package volume	0.349 m3
Package length	45
Package width	80
Package height	97
Package unit of dimension	cm
Package dimensions (LxWxH)	45x80x97 cm
Net weight	50
Net weight	50 kg
Gross weight	55
Package weight	55 kg
Unit of weight	kg
Connection power kW	10
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4
Model	Diamante