

## Induction range Metos Diamante D74/10TCII table top model, 14

The induction table top model Metos Diamante D74/10TCII has four ceramic Ø230 mm size 3,5 kW cooking zones. .Cooking zones - in which the temperature can be regulated via control knobs - have been marked on the hob made of unbreakable ceramic glass. An induction range works by only transferring inductive heat from the hob directly to the cooking vessel. Heat does not accumulate within the hob; only the bottom of the pot and the food in the pot or vessel warms up. The hob around the vessels remains cold, which makes using an induction range fast and safe. Cleaning is also easy, since food does not burn onto a cold hob.



Every detail of the strong, stylish and hygienic restaurant range series Metos Diamante 70 has been planned as an efficient and functioning solution, from pre-treatment to the preparation of the food itself, without forgetting the need to easily clean the range. Diamante 70 series ranges are available as a table top model as well as with its own cupboard, as single or multiple combined units, and are suitable for use in small to mid-sized to large kitchens. Laser cut range working surfaces allow for the seamless joining together of units into cleanly connected islands or lines in places of heavy use, such as large kitchens.

- four Ø230 mm cooking zones (3.5 kW / cooking zone)
- table model
- large splash proof control knobs
- the exterior and feet are made from stainless steel
- overheating protection

EXTRA ACCESSORIES (can be ordered separately):

- open stand
- cupboard doors

## Induction range Metos Diamante D74/10TCII table top model, 14

Item width mm	800
Item depth mm	730
Item height mm	250
Package volume	1.912
Unit of volume	m3
Package volume	1.912 m3
Package length	85
Package width	75
Package height	30
Package unit of dimension	cm
Package dimensions (LxWxH)	85x75x30 cm
Net weight	57
Net weight	57 kg
Gross weight	67
Package weight	67 kg
Unit of weight	kg
Connection power kW	14
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4
Model	Diamante