

Electric Range Metos Proxy 78ECTPT 400V3N~

Electric range Metos Proxy 78ECTPT with four round cast iron hotplates.

- Moulded top in AISI304 stainless steel with Scotch Brite finish moulded in a single piece and plates hermetically sealed guarantee easy cleaning and prevent infiltrations of grime and water
- Front control panel made of AISI304 stainless steel with Scotch Brite finish and profile designed for easy cleaning
- External panelling in stainless steel with Scotch Brite finish
- Top versions with construction designed for installation on open neutral bases or bases with doors, on refrigerated bases and on top surfaces.
- Standard h80 mm feet for flat-top installations to facilitate installation, connection and safe maintenance of the equipment
- Hotplates are hermetically secured to the top, which has a concave design to collect liquids and a smooth surface to make it easier to clean
- Four high efficiency hotplates, each 2,6kW Ø260 mm
- Power regulation on 6 levels with safety thermostat and indicator light for work control
- IPX4 water-protection rating
- does not include cord and plug

Accessories (separate price):

- JC joint cover - connection of the modules by means of a dedicated element to prevent infiltration of liquid and grime between the elements
- Neutral open stand M40
- Door for stand M40
- Closing panel for technical cabinet- in-line cooking block
- Closing panel for technical cabinet- opposite cooking block
- Front plinth M40



Electric Range Metos Proxy 78ECTPT 400V3N~

Item width mm	800
Item depth mm	700
Item height mm	295
Package volume	0.388
Unit of volume	m3
Package volume	0.388 m3
Package length	85
Package width	80
Package height	57
Package unit of dimension	cm
Package dimensions (LxWxH)	85x80x57 cm
Net weight	65
Net weight	65 kg
Gross weight	75
Package weight	75 kg
Unit of weight	kg
Connection power kW	10.4
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4
Type of electrical connection	Semifixed
Model	Proxy