

Electric grill Metos Proxy 74EGRT 400V3N~

Electric grill Metos Proxy 74EGRT with one cooking zone.

- Moulded top in AISI304 stainless steel with Scotch Brite finish moulded in a single piece guarantee easy cleaning and prevent infiltrations of grime and water
- Front control panel made of AISI304 stainless steel with Scotch Brite finish and profile designed for easy cleaning
- External panelling in stainless steel with Scotch Brite finish
- Top versions with construction designed for installation on open neutral bases or bases with doors, on refrigerated bases and on top surfaces
- Standard h80 mm feet for flat-top installations to facilitate installation, connection and safe maintenance of the equipment
- One heating zone
- Power regulation on 6 levels with maximum temperature 400°C
- Safety thermostat and indicator light
- IPX4 water-protection rating
- GN 1/1 tray with humidifier function and removable fat tray
- Tilting heating elements unit for easy cleaning and for the inspection/extraction and cleaning of the lower basin
- does not include cord and plug

Accessories (separate price):

- JC joint cover - to prevent infiltration of liquid and grime between the elements
- Door M40
- Neutral base M40
- Front plinth M40
- Closing panel for technical cabinet



Electric grill Metos Proxy 74EGRT 400V3N~

Item width mm	400
Item depth mm	700
Item height mm	295
Package volume	0.218
Unit of volume	m3
Package volume	0.218 m3
Package length	45
Package width	85
Package height	57
Package unit of dimension	cm
Package dimensions (LxWxH)	45x85x57 cm
Net weight	32.5
Net weight	32.5 kg
Gross weight	35
Package weight	35 kg
Unit of weight	kg
Connection power kW	4.08
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4
Type of electrical connection	Semifixed
Model	Proxy