

Beverage Drawer Classic

NT1200-BO2-MBO-BO2

without locks

5 drawers. The temperature range of the refrigerator is + 4 °C ... + 10°C, with the thermostat setpoint + 1 °C ... + 10°C

- smooth, insulated neutral work top
- overextending telescopic slides, can be removed for cleaning
- electronic control
- removable, water-washable condenser filter
- drainage as standard
- easily replaceable seals
- removable compressor cassette
- digital temperature display
- cast urethane insulation
- automatic defrosting and evaporation of meltwater
- stainless steel construction
- adjustable feet +20 ...- 45 mm



Beverage Drawer Classic NT1200-BO2-MBO-BO2 without locks

Item width mm	1200
Item depth mm	650
Item height mm	900
Package volume	1.001
Unit of volume	m3
Package volume	1.001 m3
Package length	123
Package width	70
Package height	110
Package unit of dimension	cm
Package dimensions (LxWxH)	123x70x110 cm
Net weight	110
Net weight	110 kg
Gross weight	130
Package weight	130 kg
Unit of weight	kg
Connection power kW	0.42
Fuse Size A	10
Connection voltage V	220-240
Number of phases	1NPE
Frequency Hz	50
Startup current A	3
Protection rating (IP)	IP43
Type of the refrigerant	R290
Quantity of refrigerant g	85
Function	cold
Power range kW	0.42
Lighting	without lighting
Stowage	drawers

Beverage Drawer Classic NT1200-BO2-MBO-BO2 without locks

Defrosting

automatic