

UltraVent exhaust hood Plus XS 6 2/3 E

The high suction power of Metos UltraVent® Plus XS hood effectively condenses steam released from the oven and filters out grease particles from the cooking air. The steam produced in the oven is conducted via the oven's steam pipe and when opening the oven door. In this case, the special filters of the UltraVent® Plus XS hood filter and break up released steam and annoying smoke produced during roasting and grilling, thereby keeping the indoor air cleaner.

The Metos UltraVent® Plus XS hood is intended for Metos SelfCooking Center XS and Metos Combimaster Plus XS oven models.

Using the integration kit (optional extra), Metos XS and UltraVent® Plus can be retrofitted.

Metos UltraVent® Plus XS hood is an excellent alternative to complex and bulky ventilation systems, as it does not require an extraction connection, rather the waste water is conducted via the oven into the drain. In addition, the hood reduces the oven's cooling requirement, thereby also reducing water consumption.

By using the Metos UltraVent® Plus XS hood, the Metos SelfCooking Center XS and Metos Combimaster Plus XS ovens can be installed even in demanding sites, such as a restaurant's open-plan kitchen or shop service desk. This fuss-free appearance of the stainless steel hood is appealing and the even surface makes it easy to keep the appliance clean.

- intended for Metos SelfCooking Center XS and Metos Combimaster Plus XS oven models
- high blowing power
- two grease filters
- the stainless steel grease filters can be washed in the



dishwasher

- no separate extraction connection needed
- automatic power increase when opening the oven door
- stainless steel structure
- intended for left-handed and right-handed ovens
- for electrical ovens
- can be retrofitted

EXTRAS (to be ordered separately)

- Integration kit UltraVent® Plus XS dishwasher
- no separate extraction connection needed
- automatic power increase when opening the oven door
- stainless steel structure
- intended for left-handed and right-handed ovens
- for electrical ovens
- can be retrofitted

EXTRAS (to be ordered separately)

- Integration kit UltraVent® Plus XS



UltraVent exhaust hood Plus XS 6 2/3 E

| Item width mm | 657 |
|----------------------------|-------------|
| Item depth mm | 580 |
| Item height mm | 329 |
| Package volume | 0.17 |
| Unit of volume | m3 |
| Package volume | 0.17 m3 |
| Package length | 71 |
| Package width | 63 |
| Package height | 38 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 71x63x38 cm |
| Net weight | 30 |
| Net weight | 30 kg |
| Gross weight | 35 |
| Package weight | 35 kg |
| Unit of weight | kg |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| | |