

## Fryer Metos Proxy 74EFRPT 10L 400V3N~

Fryer Metos Proxy 74EFRPT with one 10 liter tank.

- Moulded top in AISI304 stainless steel with Scotch Brite finish moulded in a single piece guarantee easy cleaning and prevent infiltrations of grime and water
- Front control panel made of AISI304 stainless steel with Scotch Brite finish and profile designed for easy cleaning
- External panelling in stainless steel with Scotch Brite finish
- Top versions with construction designed for installation on open neutral bases or bases with doors, on refrigerated bases and on top surfaces.
- Standard h80 mm feet for flat-top installations to facilitate installation, connection and safe maintenance of the equipment
- Frying tank volume It. 10
- with tilting power pack
- Safety thermostat for the prevention of overheating
- Oil drain provided as standard in the front in the control panel
- Indication of the minimum and maximum oil usage levels printed on the tank.
- The tanks of the gas and electric versions with external heating elements have "V" moulded tanks to facilitate cleaning
- IPx4 water-protection rating
- does not include cord and plug
- Supplied as standard with bottom grid, frying basket and tank lid

## Accessories (separate price):

- JC joint cover connection of the modules by means of a dedicated element to prevent infiltration of liquid and grime between the elements
- Neutral open stand M40
- Door for stand M40
- Closing panel for technical cabinet- in-line cooking block
- Closing panel for



technical cabinet- opposite cooking block

- Front plinth M40
- Extra basket for fryer (18x 30,5x 11 cm)
- Kit 2 Basket for fryer 2x(8,5x 30,5x 11 cm)
- Bottom grid for fryer (19,5x 37,5 cm) technical cabinet- opposite cooking block
- Front plinth M40
- Extra basket for fryer (18x 30,5x 11 cm)
- Kit 2 Basket for fryer 2x(8,5x 30,5x 11 cm)
- Bottom grid for fryer (19,5x 37,5 cm)



## Fryer Metos Proxy 74EFRPT 10L 400V3N~

Item width mm	400
Item depth mm	700
Item height mm	295
Package volume	0.223
Unit of volume	m3
Package volume	0.223 m3
Package length	46
Package width	85
Package height	57
Package unit of dimension	cm
Package dimensions (LxWxH)	46x85x57 cm
Net weight	32.5
Net weight	32.5 kg
Gross weight	35
Package weight	35 kg
Unit of weight	kg
Connection power kW	9
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Protection rating (IP)	X4
Type of electrical connection	Semifixed
Туре	electric
Model	Proxy