

Basket dispenser Metos KO/UH 50-50, heated

Basket dispenser heated by circulating air for portioning of warm food bowls

- externa measures (WxDxH): 760 x 852 x 900 mm
- continuous temperature control +20°C...+110°C
- removable stacking platform: plastic coated steel basket
- platform size 500 x 500 x 150 mm
- additional basket capacity 9 x 75 mm high, 6 x 115 mm high
- capacity depending on bowl size ca 216 pcs
- max. load 150 kg
- stainless steel structure
- universal tension spring system
- counterweight easily adjusted
- hygienic, transparent policarbonate cover supplied as standard
- electric connection: 230V, 1~, 50 Hz, 2,0 kW, spiral cable
- protection class IPX 5
- to be connected for example to the conveyor belt socket
- illuminated ON/OFF switch
- high-quality insulation
- easy to clean
- 4 corrosion resistant, maintenance free castors Ø125 mm, 2 lockable
- bumpers on each corner
- two ergonomically shaped pushing handles





Basket dispenser Metos KO/UH 50-50, heated

| Product capacity | six baskets 500×500x115 mm |
|-------------------------------|----------------------------|
| Item width mm | 850 |
| Item depth mm | 761 |
| Item height mm | 1078 |
| Package volume | 0.01 |
| Unit of volume | m3 |
| Package volume | 0.01 m3 |
| Package length | 0 |
| Package width | 0 |
| Package height | 0 |
| Package dimensions (LxWxH) | 0x0x0 |
| Net weight | 68.41 |
| Net weight | 68.41 kg |
| Gross weight | 69.41 |
| Package weight | 69.41 kg |
| Unit of weight | kg |
| Connection power kW | 2 |
| Fuse Size A | 8 |
| Connection voltage V | 230 |
| Number of phases | 1NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | X5 |
| Electrical cable length mm | 1800 |
| Type of electrical connection | Plug |
| Cleaning | hand wash |
| Function | cold+warm |
| Power range kW | 2 |
| Max load kg | 150 |