

Griddle chromium/grooved

Metos Diamante

D73/10TSFTEC1/3R table top

The Metos Diamante D73/10TSFTEC1/3R electric table top model grill has 1/3 grooved and 2/3 smooth, polished chrome plated surface. The grill has the temperature of which can be regulated between 110 °C...280 °C. The control panel has an indicator light, which illuminates when the grill zone is switched on.



Every detail of the strong, stylish and hygienic restaurant range series Metos Diamante 70 has been planned as an efficient and functioning solution, from pre-treatment to the preparation of the food itself, without forgetting the need to easily clean the range. Diamante 70 series ranges are available as a table top model as well as with its own cupboard, as single or multiple combined units, and are suitable for use in small to mid-sized to large kitchens. Laser cut hobs allow for the seamless joining together of units into cleanly connected islands or lines in places of heavy use, such as large kitchens.

- table top model
- 1/3 grooved, 2/3 smooth;
- polished chrome plated surface
- 15 mm thick cooking plate totally independent of the top
- large canal canopy along the entire perimeter of the plate for the collection of cooking residues, inclined towards the front for the decelusion of the liquids in the large drawer
- large splash proof control knobs
- exterior made from stainless steel
- overheating protection
- thermostatically controlled cooking temperature and adjustable from 110 to 280 °C
- indicator light

EXTRA ACCESSORIES (can be ordered separately):

- open cupboard
-

cupboard doors

- scrapers cupboard doors

- scrapers

Griddle chromium/grooved Metos Diamante D73/10TSFTEC1/3R table top

Item width mm	600
Item depth mm	700
Item height mm	250
Package volume	0.196
Unit of volume	m3
Package volume	0.196 m3
Package length	70
Package width	80
Package height	35
Package unit of dimension	cm
Package dimensions (LxWxH)	70x80x35 cm
Net weight	61
Net weight	61 kg
Gross weight	71
Package weight	71 kg
Unit of weight	kg
Connection power kW	7.5
Connection voltage V	400
Number of phases	3NPE
Frequency Hz	50/60
Model	Diamante