

High Speed oven Metos Merrychef Connex12 High Power S/S

The Metos Merrychef High Power ConneX®12 is the most versatile, high speed oven on the market. An all-in-one unit ideally suited to rapidly cook, toast, grill and reheat fresh or frozen food, eliminating the need for other appliances. Cooking up to 20x faster than other cooking methods it can provide hot food on demand.

- High speed Technology® combines three heat technologies: / Microwave max 2000W; Microwave setting options: Off and 5-100% in 1% increments. Microwave distribution system uses a rotating active antenna to ensure even heating throughout the food. / Convection max 2200W; Temperature setting options: Off and 100°C to 275°C in 1°C increments. / The Heat distribution system is via Tuned Impingement, ensuring the most even browning. / Combination mode 2000W+2200W
- Large cavity 30.5cm x 30.5cm to oven width 35.5cm ratio, and fits on a 600mm worktop, perfect when space is at a premium
- Easy to install due to ventless cooking capabilities through a built- in catalytic converter, eliminates the need for an extraction fan
- Cool to touch exterior makes it safe to locate anywhere with no need to allow space around the unit
- Easy to operate with a 7" HD widescreen display and new generation easyTouch®2.0, icon driven controller, ensuring consistent, high quality dishes
- Stainless steel cavity and casework, with a sealed rounded edged cavity makes it easy to clean
- Patented easy access front mounted monitored air filter
- Wi-fi/ethernet connected with access to KitchenConnect cloud for easy menu updates (or, via a USB



memory stick)

- Stainless steel finish

Included accessories / Flat cook plate / Guarded hand paddle with supporting side walls / Cooking tray, full size / Cool down pan / Cook plate liner memory stick)

- Stainless steel finish

Included accessories / Flat cook plate / Guarded hand paddle with supporting side walls / Cooking tray, full size / Cool down pan / Cook plate liner



High Speed oven Metos Merrychef Connex12 High Power S/S

| Product capacity | cavity 35,5x30,5x30,5cm |
|-------------------------------|-------------------------|
| Item width mm | 356 |
| Item depth mm | 648 |
| Item height mm | 629 |
| Package volume | 0.367 |
| Unit of volume | m3 |
| Package volume | 0.367 m3 |
| Package length | 52 |
| Package width | 82 |
| Package height | 86 |
| Package unit of dimension | cm |
| Package dimensions (LxWxH) | 52x82x86 cm |
| Net weight | 50 |
| Net weight | 50 kg |
| Gross weight | 60 |
| Package weight | 60 kg |
| Unit of weight | kg |
| Connection power kW | 6.9 |
| Fuse Size A | 32 |
| Connection voltage V | 400 |
| Number of phases | 3NPE |
| Frequency Hz | 50 |
| Protection rating (IP) | X3 |
| Electrical cable length mm | 1800 |
| Type of electrical connection | Semifixed |
| Sound level dB | 65 |