

# Bain Marie Metos Nova BM 450 LED

Cupboard for storage with doors. Doors of the cupboard are equipped with sound reducing and adjustable hinges

- standard colours of frame: high pressure laminate (M1 emission rate) grey F7912, white F1040, birch F7921 and oak F2510
- thickness of frame 18 mm
- bottom of frame made from durable veneer
- structure of the basin totally seamless and all the corners have been rounded for easier cleaning
- bain marie GN 1/1, depth 160 mm
- there is an outlet valve on the bottom of the basin with hose length of 1 m
- stainless steel fold-down tray slides on both sides, depth 250 mm
- depth of the upper tempered glass shelf is 420 mm with LED light (3000K) and works as sneeze guard
- easy rolling sturdy wheels, all of them are lockable
- includes two connecting units for binding two machines together from under the tray slides

## Accessories:

- water filling
- cover plate (200x200 mm) for the slot in the bottom board of the cupboard
- basin platform for the bottom of the basin
- cord channel in the bottom of the serving line
- special colours and materials
- tray slides out of wood
- stainless steel footing
- cover for basin
- coated picture and accent light to the one side of the machine instead of laminated panels



## Bain Marie Metos Nova BM 450 LED

|                               |              |
|-------------------------------|--------------|
| Product capacity              | 1 GN 1/1-150 |
| Item width mm                 | 465          |
| Item depth mm                 | 650/1150     |
| Item height mm                | 900/1280     |
| Package volume                | 0.752        |
| Unit of volume                | m3           |
| Package volume                | 0.752 m3     |
| Package length                | 55           |
| Package width                 | 93           |
| Package height                | 147          |
| Package unit of dimension     | cm           |
| Package dimensions (LxWxH)    | 55x93x147 cm |
| Net weight                    | 68           |
| Net weight                    | 68 kg        |
| Gross weight                  | 68           |
| Package weight                | 68 kg        |
| Unit of weight                | kg           |
| Connection power kW           | 0.556        |
| Fuse Size A                   | 10           |
| Connection voltage V          | 220-240      |
| Number of phases              | 1NPE         |
| Frequency Hz                  | 50/60        |
| Startup current A             | 2.4          |
| Protection rating (IP)        | 43           |
| Type of electrical connection | Plug         |
| Drain diameter                | 21/16        |