

# metos

## DROP-IN COLD BASIN

| CODE    | DROP IN OPENINGS |                | NET WEIGHT |
|---------|------------------|----------------|------------|
| 4138646 | DI-CB 450        | 358mm x 575mm  | 38 kg      |
| 4138656 | DI-CB 800        | 682mm x 575mm  | 47 kg      |
| 4138666 | DI-CB 1200       | 1007mm x 575mm | 56 kg      |
| 4138674 | DI-CB 1600       | 1332mm x 575mm | 65 kg      |

The length of the connection cable is 3,2 m.

When constructing the counter, an opening for the connection cable must be considered. The opening must be at least the size of a plug (diameter min. 40 mm). In addition, the edges of the opening must be finished to make sure that the connection cable is not damaged by rubbing against the opening edge.

Drain: 22/16 mm

Unit is fitted with a 1 m drain hose.

The counter, where drop-in units are installed, must be damp-proof and strong enough to bear the appliance weight.

### SERVICE- /VENTILATION DOOR

The grid must be larger in size than the condenser area, i.e. >0,09 m<sup>2</sup>. At least 50% of this area must be perforated.

Flow trough air circulation is recommended by fitting similar grid on the other side of the unit.

CB 450/CB 800/CB 1200/CB 1600

