

Bratt pan Metos Prince 60D (pan 540x530x130 mm)

Effective and user-friendly Metos Prince 60D bratt pan is equipped with electrical tilting, which makes emptying of the pan more ergonomic and effortless. The sturdy bratt pan is fixed mounted onto the floor. The seamless surfaces and rounded corners make's the pan easy to clean.

D = frying zone 540x530x130 mm.

The frying surface is made of thick steel which stores heat extremely well throughout the whole frying area. The volume of the pan area is 37 liters. The bratt pan can also be used as a bain-marie thanks to the 130 mm deep pan. The temperature is adjustable between +50°C... +250°C. The preheating time is 11 minutes (+200°C).

The bratt pan has a strong electrical tilting. Tilting cannot be started if the lid is closed or the water filling (option) is in progress. The heating elements will be switched off when the pan is tilted and will be switched on again when the pan is back in the horizontal position.

- balanced lid
- stainless steel (18/8) structure, external surfaces and lid
- uniform stainless steel frying area
- electro mechanical control
- overheating protection

FACTORY OPTIONS (to be ordered together with the bratt pan):

- height adjustment 800-950 mm
- water tap





Bratt pan Metos Prince 60D (pan 540x530x130 mm)

Product capacity	1x frying zone
Capacity	600×818×960
Item width mm	600
Item depth mm	818
Item height mm	960
Package volume	1.032
Unit of volume	m3
Package volume	1.032 m3
Package length	89
Package width	100
Package height	116
Package unit of dimension	cm
Package dimensions (LxWxH)	89x100x116 cm
Net weight	111
Net weight	111 kg
Gross weight	131
Package weight	131 kg
Unit of weight	kg
Connection power kW	7.5
Fuse Size A	16
Connection voltage V	400/230
Number of phases	3NPE
Frequency Hz	50
Startup current A	10.9
Protection rating (IP)	X3
Type of electrical connection	Fixed
Electrical conn. height mm	350
Power type	electric
Raw material	Stainless steel

Bratt pan Metos Prince 60D (pan 540x530x130 mm)

Operation type	electromechanical
Cleaning	hand wash
Temperature area °C	50-250
Pan volume L	60
Tilting	electric
Temperature probe	No
Oil filtering	No
Timer	No



User Manual SE



METOS PRINCE



